

olivetti



d-COLOR P126W and P126

COLOUR DIGITAL PRINTERS

The Olivetti d-Color P126W and P126 network printers are intended for individual users and workgroups looking for a **professional colour device offering outstanding productivity at an affordable cost.**

Both models deliver speeds of 26 ppm on colour jobs and 32 ppm for b&w, with a first page out time of just 9 seconds in colour and 8 seconds in b&w.

The **wide range of options** includes a duplex, a second paper tray, a memory expansion and a 40 GB hard disk (for the P126 only).

The d-Color P126W and P126 printers offer respectively 64 MB and 256 MB memory capacity, a 200 MHz and a 500 MHz processor, and GDI and PCL/PostScript print languages.

Running costs are kept to a minimum with high-capacity toner cartridges (8,000 pages in b&w, 6,000 pages in colour) and long-life drums.

COLOUR PRINTING SPEED 26 ppm

FIRST PAGE OUT IN JUST 8 SECONDS

SUPERIOR PRINT QUALITY FOR COLOUR AND FOR B&W

OPTIONAL DUPLEX FOR FRONT/BACK PRINTING

PAPER CAPACITY UP TO 930 CUT SHEETS

WINDOWS AND MACINTOSH COMPATIBILITY

INTEGRATED NETWORK CONNECTIVITY

LOW RUNNING COSTS



LCD DISPLAY with toner status indicator



Optional 530-sheet SECOND TRAY



MANUAL FEED for flexible media handling

TECHNICAL SPECIFICATIONS

PRINTER	Technology speed (A4)	Up to 26 ppm colour and 32 ppm b&w	Processor speed	P126W: 200 MHz P126: 500 MHz
	Time to first print	< 9 seconds colour and 8 seconds b&w	Operating Systems	Windows 2000/ XP Home/XP Professional/XP Professional x64 / Server 2003 / Server 2003 for x64 / Vista (32-bit) / Vista (64-bit); Mac OS X Intel 10.4.4 or greater
	Warm-up time	Up to 60 seconds from power on Up to 45 seconds from power save		
	RAM	P126W: 64 MB (max 320 MB) P126: 256 MB (max 768 MB)	Utility	P126W: LPR (Windows only), Operator Panel Download, Silex Admin Manager P126: LPR (Windows only) Silex Admin Manager, Storage Device Manager, Profile Assistant
	Hard disk	P126: 40 GB (optional)		
	Resolution	1200x600 dpi multi-level technology	Font	P126W: N.A. P126: 87 scalable PCL and 136 PostScript; Line Printer, OCR A/B and USPS Barcodes
	Image enhancements	Auto Colour Balance, Photo Enhance via driver (except Mac and PostScript drivers)	Emulations	P126W: Windows/Mac Host based printing system P126: PCL 6 (XL 3.0 or PCL 5c), PostScript 3 (compatible), SIDM (IBM-PPR, EPSON FX)
	Interfaces	USB 2.0 (high speed), Ethernet 10/100 BASE-TX		
PAPER HANDLING	Paper tray	300 sheets (80 g/m ²) Paper format A4, A5, B5, A6, Legal 13, Legal 13,5, Legal 14, Letter, Executive	Duplex	Optional Paper format: A4, A5, B5, Legal 13, Legal 13,5, Legal 14, Letter, Executive, custom
	Optional second tray	530 sheets (80 g/m ²) Paper format A4, A5, B5, Legal 13, Legal 13,5, Legal 14, Letter, Executive	Paper weight	Standard tray: 64-120 g/m ² Optional tray: 64-176 g/m ² Multi-purpose feeder: 75-203 g/m ² Duplex: 75-105 g/m ²
	Multi-purpose feeder	100 sheets (80 g/m ²) Paper format: A4, A5, B5, A6, 10 envelopes, labels, Custom size (up to 1200 mm length including banners), 50 transparencies	Paper output capacity	250 sheets face-down, 100 sheets face-up (80 g/m ²)
GENERAL	Duty cycle	Max 60,000 pages/month A4	Dimensions (WxDxH)	400 (max. 435) x 528 (max. 563.5) x 339.5 mm
	Noise level	Operating: < 55,6 dB(A) Stand-by: < 37 dB(A) Power saving: background level		
	Power consumption	Typical: 490 W Peak: 1200 W Idle: 100 W (average) Power saving < 15 W	Consumables (5% covering)	First equipment CMYK toner: up to 2,250 pages Standard Black Toner: up to 8,000 pages CMY Toner: up to 6,000 pages A4 CMYK Drum: up to 20,000 pages A4 Transfer Belt: 60,000 pages A4 Fuser unit: 60,000 pages A4
	Power supply	220-240V, frequency 50/60 Hz +/-2%		

Product performances are referred to an appropriate use under optimal conditions. With the right to change technical specifications. The registered trademarks are the property of their respective owners. d-Color P126W and P126 are distributed by Olivetti S.p.A. (01/09) - Code: 26783-01